

# POS PRINTER



## SLK-TE212 II

- Energy star qualified for power efficiency
- High speed printing : Max. 220mm/sec
- Paper width adjustable 50~82.5mm
- ESC/POS command compatible
- Printing notice accessory : Melody box
- Wall mount installation available



### APPLICATIONS



Shopping



Mart



Airport



Hospital



Coffee Shop



Bank



Restaurant



Ticketing



Parking




Lottery



Election

## HIGH SPEED DESKTOP THERMAL POS PRINTER

# SLK-TE212 II



MODEL		SLK-TE212 II
PRINTING	METHOD	Direct Thermal
	SPEED	Max. 220mm/sec
	WIDTH	72mm(512 Dots/Line)
	RESOLUTION	180DPI / 203DPI(Optional)
PAPER	TYPE	Thermal Paper / Linerless(Optional)
	WIDTH	50mm ~ 82.5mm
	THICKNESS	0.06mm ~ 0.09mm
	ROLL DIAMETER	Max. ø 80.0mm
	ROLL CORE INNER	12.5mm ± 0.5mm
RELIABILITY	TPH LIFE	160Km
	MCBF	60,000,000Lines
AUTO CUTTER		1,800,000cuts(Guillotine)
SENSOR	STANDARD	Paper End, Paper Low, Cover Open
	OPTION	Black Mark
INTERFACE		USB (USB(B type) plus one more card selectable [Serial(RS-232C), Parallel(IEEE1284), Ethernet, Wi-Fi(802.11a/b/g/n), Bluetooth Ver2.1(IOS)]
EMULATION		ESC/POS Command Compatible
DRIVER		Windows Driver(10, 2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Window CE & Mobile Driver & SDK(CE 4.2~, Mobile 5.0~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1~) SDK, Blackberry SDK, Symbian
POWER	TYPE	External SMPS
	AC	100 ~ 240Vac 50/60 Hz
	DC	24Vdc / 1.75A
TEMPERATURE	OPERATION	0 ~ 45°C
	STORAGE	-20 ~ 60°C
DIMENSION		152 × 204 × 150 mm (W × D × H )
WEIGHT		1.7kg
COLOR		Cool grey, Ivory

### INTERFACE



### ACCESSORY



Melody box

● All specification and desings are subject to change without notice.

**A ROOT**  
Aroot Co., Ltd.

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T.+82-31-8077-5000 F.+82-31-624-5310

www.miniprinter.com



**SEWOO**